

Bowl cutter twin SM-ZW 45/114 T2M-R

Datasheet

Special version: drives of bowl cutter and grinder are locked against each other and cannot be used simultaneously!

type code	444	
option model	standard	reinforced drive
Electrical data		
operating voltage (standard)	400V/50Hz	
rated power	9 kW	12 kW
obligatory pre-fusing at customer site ¹⁾	25 A gL/gG	35 A gL/gG
rotation speed		
knives head	1200/2400 min ⁻¹	1500/3000 min ⁻¹ 1800/3600 min ⁻¹ (optional)
mixing (forward and backward)	75/150 min ⁻¹	
bowl	9/18 min ⁻¹	
throughput grinder	up to 25 kg/min	
optimum batch size		
boiled sausages	36 kg	
cooked sausages	32 kg	
raw sausages	20 kg	
weight⁵⁾	890 kg	920 kg

Bowl cutter twin SM-ZW 45/114 T2M-R

Datasheet

Standard version: drives of bowl cutter and grinder are not locked against each other and **can be used simultaneously!**

type code	444	
option model	standard	reinforced drive
Electrical data		
operating voltage (standard)	400V/50Hz	
rated power	14,5 kW	17,5 kW
obligatory pre-fusing at customer site ¹⁾	35 A gL/gG	50 A gL/gG
rotation speed		
knives head	1200/2400 min ⁻¹	1500/3000 min ⁻¹ 1800/3600 min ⁻¹ (optional)
mixing (forward and backward)	75/150 min ⁻¹	
bowl	9/18 min ⁻¹	
throughput grinder	up to 25 kg/min	
optimum batch size		
boiled sausages	36 kg	
cooked sausages	32 kg	
raw sausages	20 kg	
weight ⁵⁾	890 kg	920 kg